

"Innovations in Infrastructure Repair Technology"

PRIME RESINS, INC.

OFFICE:(770) 388-0626 / FAX (770) 388-0936

2291 Plunkett Road

Conyers (Atlanta), Georgia 30012

SECTION I - IDENTITY INFORMATION

PRODUCT NAME: **SPEED BOND #1 COMPONENT B**

MANUFACTURER: **PRIME RESINS, INC.**
ADDRESS: 2291 PLUNKETT ROAD

FAMILY/CHEMICAL NAME: POLY AMIDO AMINE

CITY: CONYERS (ATLANTA) STATE: GEORGIA ZIP CODE: 30012

PRODUCT TYPE: EPOXY RESIN HARDENER

TELEPHONE: (770) 388-0626 FAX: (770) 388-0936

DOT CATEGORY: CORROSIVE LIQUID N.O.S.

EMERGENCY: **CHEMTREK (800) 424-9300**

PREPARED BY: ATO WILBERFORCE

SECTION II - HAZARDOUS INGREDIENTS

| COMPONENTS:(CHEMICAL IDENTITY);COMMON NAME(S) | LIMITS | CAS NUMBER |
|---|--|------------|
| ALKYLATED PHENOL | ACGIH(TLV) NOT ESTABLISHED OSHA(PEL) NOT ESTABLISHED | 84852-15-3 |
| . | OSHA(STEL) NOT ESTABLISHED | |
| ETHYLENE AMINE | ACGIH(TLV) NOT ESTABLISHED OSHA(PEL-STEL) NOT ESTABLISHED | 140-31-8 |
| | LD1620 MG/KG (ORAL RAT) | |
| CARBON BLACK AS POWDERS, CONSIDERED A NUISANCE DUST UNDER 29CFR1910.1200 | SARA TITLE III SECT. 313: NOT A CANCER SUSPECT | 1333-86-4 |
| | | |
| | | |

SECTION III - PHYSICAL DATA

VAPOR PRESSURE:(AIR=1) NOT DETERMINED

BOILING POINT: NOT DETERMINED

VAPOR DENSITY:(AIR=1) NOT DETERMINED

WATER SOLUBILITY: SLIGHT

DENSITY: 8.2 LBS/GAL

SPECIFIC GRAVITY:(H2O=1) @77° F 0.98

APPEARANCE(SOLID,LIQUID,GAS,COLOR) AND ODOR:

BLACK, AMMONIA SMELLING PASTE

EVAPORATION RATE(BUTYL ACETATE=1): SLOWER

SECTION IV - FIRE AND EXPLOSION DATA

FLASH POINT: > 383° F PENSKEY MARTIN CLOSED CUP

EXTINGUISHING MEDIA: CO2-DRY CHEMICAL-FOAM-WATER SPRAY

SPECIAL FIRE FIGHTING PROCEDURES: USE SELF- CONTAINED BREATHING APPARATUS

UNUSUAL FIRE AND EXPLOSION HAZARDS:DECOMPOSITION & COMBUSTION PRODUCTS MAY BE TOXIC. COOL FIRE EXPOSED CONTAINERS WITH WATER.

HEALTH **3** **FLAMMABILITY** **0** **REACTIVITY** **0** **PERSONAL PROTECTION** **C**

SECTION V - REACTIVITY DATA

| | | | |
|--------------------------|----------|---|--|
| STABILITY: | STABLE | X | CONDITIONS TO AVOID: ELEVATED TEMPERATURES |
| | UNSTABLE | | |
| HAZARDOUS POLYMERIZATION | | | |
| MAY OCCUR | | | |
| WILL NOT OCCUR | | X | |

INCOMPATIBILITY: STRONG OXIDIZING AGENTS, MINERAL ACIDS, AND EPOXY RESINS UNDER UNCONTROLLED CONDITIONS.

HAZARDOUS DECOMPOSITION: CARBON MONOXIDE, CARBON DIOXIDE, AND OXIDES OF NITROGEN.

SECTION VI - HEALTH HAZARD DATA

| | | | | | | |
|-------------------|------|---|---|------------|---|---|
| ROUTE(S) OF ENTRY | SKIN | X | X | INGESTION | X | EXPOSURE EFFECTS: IRRITATION, SENSITIZATION, DERMATITIS |
| | EYES | X | | INHALATION | X | |

ACUTE HAZARDS: WILL CAUSE BURNS TO SKIN AND EYES. HIGH CONCENTRATIONS OF VAPOR CAUSE IRRITATION OF RESPIRATORY TRACT.

CHRONIC HAZARDS: PROLONGED OR REPEATED EXPOSURE MAY CAUSE ASTHMA AND SKIN SENSITIZATION OR OTHER ALLERGIC RESPONSE.

| | |
|------------------------------------|---|
| EMERGENCY AND FIRST AID PROCEDURES | EYES: IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST FIFTEEN MINUTES. PROMPT MEDICAL CONSULTATION IS ESSENTIAL. |
| | SKIN: PROMPTLY WASH WITH MILD SOAP AND WATER. |
| | INHALATION: REMOVE TO FRESH AIR. GIVE OXYGEN IF NECESSARY. GET MEDICAL ATTENTION. |
| | INGESTION: GET MEDICAL; ATTENTION. DO NOT INDUCE VOMITING. IT WILL CAUSE FURTHER DAMAGE TO THROAT. |
| | OTHER: WASH CONTAMINATED CLOTHING BEFORE REUSE. DISCARD CONTAMINATED SHOES AND OTHER LEATHER ARTICLES. |

SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE

STEPS TAKEN FOR SPILLS OR RELEASE: AVOID ALL PERSONAL CONTACT. TAKE UP WITH ABSORBENT MATERIAL. SHOVEL INTO CLOSEABLE CONTAINER. FLUSH CONTAMINATED AREA WITH WATER. DO NOT FLUSH TO STORM DRAINS OR WATER SUPPLIES.

WASTE DISPOSAL METHOD: DISPOSE OF AS A HAZARDOUS WASTE IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS

PRECAUTIONS FOR HANDLING, SHIPPING, STORING, AND OTHER: AVOID CONTACT WITH EYES, SKIN OR CLOTHING. AVOID BREATHING VAPORS, MIST, OR SPRAY. USE WITH GOOD POSITIVE VENTILATION.

STORE IN A COOL, DRY AREA IN CLOSED CONTAINERS. OBSERVE CONDITIONS OF GOOD INDUSTRIAL HYGIENE AND SAFE WORK PRACTICE.

WARNING: MAY CAUSE IRRITATION AND/OR SKIN REACTION.

SECTION VIII - CONTROL MEASURES

RESPIRATORY PROTECTION: NIOSH APPROVED RESPIRATORY PROTECTION REQUIRED IN THE ABSENCE OF GOOD GENERAL MECHANICAL VENTILATION AND LOCAL EXHAUST.

| | | |
|---------------------|---|---|
| PROTECTIVE CLOTHING | EYES: SPLASH PROOF GOGGLES OR SAFETY GLASSES WITH SIDE SHIELDS. | CLOTHING: LONG LEGGED AND SLEEVED CLOTHING. |
| | GLOVES: IMPERVIOUS GLOVES, NEOPRENE OR RUBBER | SHOES: CHEMICAL RESISTANT LEATHER |

SECTION IX - REGULATORY INFORMATION

| | | |
|-----------------------|--|--|
| ISSUE DATE: 7/7/94 | DOT CLASS: CLASS 8 CORROSIVE LIQUID N.O.S. UN 1760 | CERCLA STATUS: NOT LISTED |
| REVISION: 1/17/05 | RCRA STATUS: NOT LISTED | TSCA INVENTORY STATUS: CHEMICAL COMPONENTS LISTED ON INVENTORY (PENNSYLVANIA RIGHT TO KNOW ACT) |

THIS INFORMATION AND RECOMMENDATIONS CONTAINED HEREIN ARE BASED UPON DATA BELIEVED TO BE CORRECT. HOWEVER, NO GUARANTEE OR WARRANTY OF ANY KIND EXPRESSED OR IMPLIED IS MADE WITH RESPECT TO THE INFORMATION CONTAINED HEREIN.

