



Prime Flush 2

Polymer Flushing Solvent

Prime Flush 2 is formulated for the flushing of polyurethane and polyester mixing / dispensing equipment. This product was developed as a more effective replacement for DBE, Citrus-based, and other low-cost flushing solvents. Like these flushing materials, the Prime Flush 2 flushing solvent is also a low-cost option. It is a low-toxicity, non-chlorinated, non-flammable solvent also designed to replace solvents such as acetone, methylene chloride, and other chlorinated solvents used in polyurethane and polyester flushing applications. Prime Flush 2 can be strained and recycled for reuse.

**New
Organic-Based,
Non-Flammable,
Reuseable
Formula!**

USES:

- Cleaning Equipment
- Flushing Pump Lines and Hoses of uncured polyurethane foam, polyester resins, polyurethane reactive hot melts, most polyurethane adhesives, and rigid and flexible urethanes
- Effective for the flushing of various other polymers including epoxies, acrylics, and methacrylates

DIRECTIONS FOR USE:

Prime Flush 2 can be used at room temperature or heated. For most flushing applications, the solvent can be heated to 150-175°F to increase effectiveness. In flushing, use the solvent as you would any other flushing agent. Prime Flush 2 is safe to use as a flushing solvent on equipment using Viton seals as long as the solvent is not left in contact with the Viton for an extended period of time. After 24 hours, Viton may begin to swell if left immersed in Prime Flush 2.

PRODUCT CAUTIONS:

Prime Flush 2 contains powerful organic solvents. It is harmful if inhaled or swallowed. Avoid breathing vapors or mist. Keep away from heat and flame. Avoid contact with eyes and skin. Wear gloves, safety goggles, and protective clothing when handling. Use with adequate ventilation. Refer to MSDS before use, for disposal, or for additional information on safe handling.

PACKAGING:

5 gallon units