Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier	985LXA-SDS	Revision Date:	02/18/2021
	Product Name:	Prime Flex LX(10) & LX(20) Component A	Supersedes Date:	02/18/2021
1.2	Relevant identified uses of the substance or mixture and uses advised against	See Technical Datasheet. For use t against: Home DIY applications. Ad additional hazards.		
1.3	Details of the supplier of the safety	v data sheet		
	Supplier:	Prime Resins Inc. 2291 Plunkett Road Conyers, GA 30012 USA Phone: 800-321-7212 Fax: 770-338-0936 www.primeresins.com		
	Datasheet Produced by:	EHS@primeresins.com		
1.4	Emergency telephone number:	CHEMTREC +001 703 5273887 (Ou CHEMTREC 1-800-424-9300 (Inside	,	

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 2 Eye Irritation, category 2 Respiratory Sensitizer, category 1 STOT, repeated exposure, category 2 STOT, single exposure, category 3, RTI Skin Irritation, category 2 Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

4,4'-methylenediphenyl diisocyanate, Diphenylmethane-diisocyanate, isomers and homologues

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing
	11005	difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.
PRECAUTION PHRASES		
	P260	Do not breathe dust/fume/gas/mist/vapours/spray.
	P280	Wear protective gloves/protective clothing/eye protection/ face protection.
	P284	Wear respiratory protection.
	P285	In case of inadequate ventilation wear respiratory protection.
	P302+352	IF ON SKIN: Wash with plenty of soap and water.
	P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
	P308+313	IF exposed or concerned: Get medical advice/attention.
	P314	Get medical advice/attention if you feel unwell.
	P333+313	If skin irritation or rash occurs: Get medical advice/attention.
	P341	If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
	P342+311	If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

2.3 Other hazards

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.

Chemical Name

101-68-8 9016-87-9	50 - <75 50 - <75		
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
101-68-8	GHS07-GHS08	H315-317-319-332-334-335-351-373	0

101-68-8	GHS07-GHS08	H315-317-319-332-334-335-351-373	0
9016-87-9	GHS07-GHS08	H315-317-319-332-334-335-351-373	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Do not use solvent or thinners to clean skin. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. AFTER EYE CONTACT: Consult a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. Harmful by inhalation. Irritating to respiratory system. Limited evidence of a carcinogenic effect. Irritating to eyes and skin. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire. Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide, nitrogen oxide, cyanides, isocyanate vapours. Reacts violently with water.

5.3 Advice for firefighters

Use water spray to cool unopened containers. Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. For personal protection see section 8.2. Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Discharge into the environment must be avoided. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: People handling polyurethane products must have received special training according to guidelines from the National Occupational Health and Safety Board. Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Apply technical measures to comply with the occupational exposure limits (see section 8).

PROTECTION AND HYGIENE MEASURES: Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze. **STORAGE CONDITIONS:** Keep out of the reach of children. Keep at temperatures between 10 and 30 °C. Store in original container. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.3 Specific end use(s)

Component of multicomponent coatings. The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(JS)	
	, כ	

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
4,4'-methylenediphenyl diisocyanate	101-68-8	0.005 PPM		
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9			
Name	CAS-No.	OSHA PEL	OSHA STEL	
Name 4,4'-methylenediphenyl diisocyanate	<u>CAS-No.</u> 101-68-8	OSHA PEL 0.02 PPM-CEILIN	<u>OSHA STEL</u>	

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment. Combination filter: A2-P2.

EYE PROTECTION: Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Isocyanates can harden gloves and increase the risk of their splitting. Protective gloves complying with EN 374: Viton®, Neoprene, Nitril rubber, Butyl rubber. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** At temperatures below 30°C, provide a good standard of general ventilation. At temperatures over 30°C - and always if sprayed - exhaust ventilation is required. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Brown liquid
	Physical State	Liquid
	Odor	Mild
	Odor threshold	Not determined
	рН	Not determined
	Melting point / freezing point (°C)	Not determined
	Boiling point/range (°C)	N.D N.D.
	Flash Point, (°F / °C)	Not determined
	Evaporation rate	Not determined
	Flammability (solid, gas)	Not determined
	Upper/lower flammability or explosive limits - %(V)	Not determined
	Vapour Pressure	Not determined
	Vapour density	Not determined
	Relative density	Not determined
	Solubility in / Miscibility with water	Not determined
	Partition coefficient: n-octanol/water	Not determined
	Auto-ignition temperature (°C)	Not determined
	Decomposition temperature (°C)	Not determined
	Viscosity	200 cP
	Explosive properties	Not determined
	Oxidising properties	Not determined
9.2	Other information	
	VOC Content g/l:	Not determined
	Specific Gravity (g/cm3)	1.230

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.3 Possibility of hazardous reactions

Polymerises at about 200°C with evolution of CO2. Amines and alcohols cause exothermic reactions. Preparation reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze.

10.5 Incompatible materials

Keep away from oxidising agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Preparation reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:	
Oral LD50:	No information available.
Inhalation LC50:	No information available.
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
101-68-8	4,4'-methylenediphenyl diisocyanate	15000 mg/kg oral	>9400 mg/kg	43 ppm vapor 4 hrs	0.000	0.000
9016-87-9	Diphenylmethane-diisocyanate, isomers and homologues	>10000 mg/kg	>9400 mg/kg	049 mg/l (4 h, Aerosol. rat)		

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Isocyanates may cause acute irritation and/or sensitisation of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition.

12.	Ecol	ogical Information					
12.1	Toxic	ity:					
	EC	50 48hr (Daphnia):	No inf	ormation			
	IC	50 72hr (Algae):	No in	formation			
	LC	50 96hr (fish):	No in	formation			
12.2	Persi	stence and degradability:	No in	formation			
12.3 Bioaccumulative potential:		No in	No information				
12.4	Mobil	ity in soil:	No in	formation			
12.5		ts of PBT and vPvB sment:	The p	roduct does not mee	t the criteria for PBT/VF	PvB in accordance with Ann	ex XII
12.6	Other	adverse effects:	No in	formation			
CAS-	No.	Chemical Name		<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>	
101-6	68-8	4,4'-methylenediphenyl diisocyanate		>1000 mg/l	No information	>1000 mg/l	
9016	-87-9	Diphenylmethane-diisocyanate, isomohomologues	ers and	No information	1640 mg/l	>1000 mg/l	

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Dispose of waste material at an approved hazardous waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Contaminated packaging to be disposed of as product. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

14. Transport Information

14.1	UN number	Not applicable
14.2	UN proper shipping name	Not regulated for transport according to U.S. DOT, ADR/RID, IMDG, and IATA regulations.
	Technical name	Not applicable
14.3	Transport hazard class(es)	Not applicable
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	Not applicable
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
	EmS-No.:	Not applicable
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u>	CAS-No.	<u>%</u>
4,4'-methylenediphenyl diisocyanate	101-68-8	50
Diphenylmethane-diisocyanate, isomers and homologues	9016-87-9	50

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:	Not applicable
EPA VOC Content Limit (g/l):	Not determined
Product VOC Content (g/l)	Not applicable
Thinning Recommendations:	Not applicable
Application Recommendations:	Not applicable

* As per the federal EPA definition for coating categories in 40 CFR 59.401.

** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product. California Proposition 65:

No Proposition 65 Chemicals exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 14 - Transportation Information

•

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
US CAS EINECS REACH GHS LTEL STEL OEL ppm mg/m3 TLV	United States Chemical Abstract Service European Inventory of Existing Chemical Substances Registration, Evaluation, Authorization of Chemicals Regulation Globally Harmonized System of Classification and Labeling of Chemicals Long term exposure limit Short term exposure limit Occupational exposure limit Parts per million Milligrams per cubic meter Threshold Limit Value

Date Printed: 02/19/2021

OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
modified by the Pr	cotocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1	Product Identifier Product Name:	RM-PFLX10 B Prime Flex 985 LX10 Component	Revision Date: Supersedes Date:	02/18/2021 10/10/2018
1.2	Relevant identified uses of the substance or mixture and uses advised against	B Polyol MixtureFor use by appropriately application, because of the additional		Advised against: Spray
1.3	Details of the supplier of the safety	data sheet		
	Supplier:	Prime Resins Inc. 2291 Plunkett Road Conyers, GA 30012 USA Phone: 800-321-7212 Fax: 770-338-0936 www.primeresins.com		
	Datasheet Produced by:	EHS@primeresins.com		
1.4	Emergency telephone number:	CHEMTREC +001 703 5273887 (Outs CHEMTREC 1-800-424-9300 (Inside I		
2. I	Hazard Identification			

2.1 Classification of the substance or mixture

Flammable Liquid, category 2

2.2 Label elements

Symbol(s) of Product



Signal Word Danger

Named Chemicals on Label None

HAZARD STATEMENTS

Flammable Liquid, category 2 PRECAUTION PHRASES	H225	Highly flammable liquid and vapour.
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P235	Keep cool.
	P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

<u>CAS-No.</u> 25322-69-4	Chemical Name polypropylene glycol		<u>%</u> 10 - <25 2.5 - <10 1.0 - <2.5
280-57-9	triethylenediamine		0.1 - <1.0
CAS-No.	GHS Symbols	GHS Hazard Statements	M-Factors
25322-69-4	GHS07	H302	0
	GHS02	H225-412	0
	GHS02-GHS07-GHS08-GHS09	H225-304-315-336-411	0
280-57-9	GHS07	H302-312-315-319-332	0

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Consult a physician after significant exposure.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.

AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

No Information

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

FOR SAFETY REASONS NOT TO BE USED: Alconol, Alconol based solutions, any other media not lis

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

Flash back possible over considerable distance. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment. Remove all sources of ignition.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapours). Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limits. Electrical equipment should be protected to the appropriate standard. Preparation may charge electrostatically: always use earthing leads when transferring from one container to another. Use only in area provided with appropriate exhaust ventilation. To avoid ignition of vapours by static electricity discharge, all metal parts of the equipment must be grounded. Wear personal protective equipment. Do not breathe vapours or spray mist. Use only explosion-proof equipment. Keep away from sources of ignition - No smoking.

PROTECTION AND HYGIENE MEASURES: Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

Name	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
polypropylene glycol	25322-69-4			
triethylenediamine	280-57-9			
News				
Name	<u>CAS-NO.</u>	<u>OSHA PEL</u>	<u>OSHA STEL</u>	
polypropylene glycol	25322-69-4			
triethylenediamine	280-57-9			

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: Respirator with a vapor filter.

EYE PROTECTION: Tightly fitting safety goggles.

HAND PROTECTION: Impervious gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: No Information

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

9.1	Information on basic physical and chemical properties Appearance:	Not determined
	Physical State	Liquid
	Odor	Slightly sweet
	Odor threshold	Not determined
	рН	Not determined
	Melting point / freezing point (°C)	Not determined
	Boiling point/range (°C)	49 - N.D.
	Flash Point, (°F / °C)	Not determined
	Evaporation rate	Not determined
	Flammability (solid, gas)	Not determined

Upper/lower flammability or explosive limits - %(V)	Not determined
Vapour Pressure	Not determined
Vapour density	Not determined
Relative density	1.051
Solubility in / Miscibility with water	Not determined
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	Not determined
Viscosity	500 cps
Explosive properties	Not determined
Oxidising properties	Not determined
Other information	
VOC Content g/l:	Not determined
Specific Gravity (g/cm3)	1.053

10. Stability and Reactivity

10.1 Reactivity

9.2

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Risk of ignition.

10.3 Possibility of hazardous reactions Hazardous polymerisation does not occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:	
Oral LD50:	No information available.
Inhalation LC50:	No information available.
Irritation:	No information available.
Corrosivity:	No information available.
Sensitization:	No information available.
Repeated dose toxicity:	No information available.
Carcinogenicity:	No information available.
Mutagenicity:	No information available.
Toxicity for reproduction:	No information available.
STOT-single exposure:	No information available.
STOT-repeated exposure:	No information available.
Aspiration hazard:	No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25322-69-4	polypropylene glycol	681 mg/kg			0.000	0.000
Additional Information:						

No Information

12. Ecological Information

12.1	Toxicity:	
	EC50 48hr (Daphnia):	No information
	IC50 72hr (Algae):	No information
	LC50 96hr (fish):	No information
12.2	Persistence and degradability:	No information
12.3	Bioaccumulative potential:	No information
12.4	Mobility in soil:	No information
12.5	Results of PBT and vPvB assessment:	The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

12.6 Other adverse effects: No information IC50 72hr CAS-No. **Chemical Name** EC50 48hr LC50 96hr 25322-69-4 polypropylene glycol No information 280-57-9 triethylenediamine No information No information No information

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information		
14.1	UN number	UN1866
14.2	UN proper shipping name	Resin solution, flammable
	Technical name	Not applicable
14.3	Transport hazard class(es)	3
	Subsidiary shipping hazard	Not applicable
14.4	Packing group	II
14.5	Environmental hazards	Not applicable
14.6	Special precautions for user	Not applicable
	EmS-No.:	Not applicable
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Flammable (gases, aerosols, liquids, or solids)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name

CAS-No.

<u>%</u>

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:	Not applicable
EPA VOC Content Limit (g/I):	Not determined
Product VOC Content (g/I)	Not applicable
Thinning Recommendations:	Not applicable
Application Recommendations:	Not applicable

* As per the federal EPA definition for coating categories in 40 CFR 59.401.

** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name	CAS-No.
D-Glucitol, propoxylated	52625-13-5
Oxirane, 2-methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1)	9082-00-2
tris(2-chloroisopropyl) phosphate	13674-84-5
Pennsylvania Right-To-Know	

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name	CAS-No.
D-Glucitol, propoxylated	52625-13-5
Oxirane, 2-methyl-, polymer with oxirane, ether with 1,2,3-propanetriol (3:1)	9082-00-2
tris(2-chloroisopropyl) phosphate	13674-84-5
California Proposition 65:	

No Proposition 65 Chemicals exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

Highly flammable liquid and vapour. Harmful if swallowed.

H225 H302

Page 8 / 10

H304	May be fatal if swallowed and enters airways.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H336	May cause drowsiness or dizziness.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

Revision Description Changed Composition Information Changed Substance and/or Product Properties Changed in Section(s): 01 - Identification 09 - Physical and Chemical Properties

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830; European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission
EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations

Date Printed: 02/19/2021

IMDG IATA	International Maritime Dangerous Goods Code International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as
	Protocol of 1978
IBC	International Bulk Container
RTI	Respiratory Tract Irritation
NE	Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.