Safety Data Sheet Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier RM-3000FA Revision Date: 02/26/2021

Product Name: Prime Bond 3000 Fast Supersedes Date: 11/02/2020

Component A

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Professional use only. See Technical Datasheet. Manual activities involving hand contact. For use by appropriately trained applicators. Advised against: Home DIY applications. Component of multi-component industrial grouts, mortars and screeds.

1.3 Details of the supplier of the safety data sheet

Supplier: Prime Resins Inc.

2291 Plunkett Road Conyers, GA 30012

USA

Phone: 800-321-7212 Fax: 770-338-0936 www.primeresins.com

Datasheet Produced by: EHS@primeresins.com

1.4 Emergency telephone number: CHEMTREC +001 703 5273887 (Outside US)

CHEMTREC 1-800-424-9300 (Inside US)

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Chronic, category 2
Carcinogenicity, category 2
Eye Irritation, category 2
Germ Cell Mutagenicity, category 2
STOT, single exposure, category 3, RTI
Skin Irritation, category 2
Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Warning

Named Chemicals on Label

Butyl glycidyl ether, Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700), phenol, polymer with formaldehyde, glycidyl ether

HAZARD STATEMENTS

Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Germ Cell Mutagenicity, category 2	H341	Suspected of causing genetic defects.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P308+313	IF exposed or concerned: Get medical advice/attention.
P308+P313	IF exposed or concerned: Get medical advice/attention
P333+313 P391 P405	If skin irritation or rash occurs: Get medical advice/attention. Collect spillage. Store locked up.
P333+313 P391	If skin irritation or rash occurs: Get medical advice/attention.

2.3 Other hazards

Ingestion may cause irritation to mucous membranes.

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous Ingredients

CAS-No.Chemical Name%25068-38-6Reaction product: bisphenol-A-(epichlorhydrin) epoxy resin (number average molecular weight <= 700)</td>50 - <75</td>

28064-14-4 phenol, polymer with formaldehyde, glycidyl ether 25 - <50 2426-08-6 Butyl glycidyl ether 2.5 - <10

GHS Symbols CAS-No. **GHS Hazard Statements** M-Factors 25068-38-6 **GHS07-GHS09** H315-317-319-335-411 0 28064-14-4 GHS07-GHS09 H315-317-319-411 0 2426-08-6 GHS02-GHS07-GHS08 0 H226-302-317-332-335-341-351-412

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Do not use solvent or thinners to clean skin. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. AFTER EYE CONTACT: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.

AFTER INGESTION: Consult a physician. Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Never give anything by mouth to an unconscious person. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause sensitization by skin contact. Irritating to eyes and skin.

4.3 Indication of any immediate medical attention and special treatment needed

Treat symptomatically. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire. Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke).

5.3 Advice for firefighters

Keep containers and surroundings cool with water spray. In the event of fire, wear self-contained breathing apparatus. Do not use a solid water stream as it may scatter and spread fire. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. For personal protection see section 8.2. Ensure adequate ventilation. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Discharge into the environment must be avoided. Do not allow material to contaminate ground water system. Prevent product

from entering drains. Local authorities should be advised if significant spillages cannot be contained. May cause long-term adverse effects in the aquatic environment.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: People handling epoxy products must have received special training according to guidelines from the National Occupational Health and Safety Board. Wear personal protective equipment. Avoid contact with skin and eyes. Apply technical measures to comply with the occupational exposure limits (see section 8). PROTECTION AND HYGIENE MEASURES: Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze. **STORAGE CONDITIONS:** Keep out of the reach of children. Keep at temperatures between 10 and 25 °C. Store in original container. Keep container tightly closed in a dry and well-ventilated place. Keep away from food, drink and animal feeding stuffs.

7.3 Specific end use(s)

Component of multicomponent coatings. The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6			
phenol, polymer with formaldehyde, glycidyl ether	28064-14-4			
Butyl glycidyl ether	2426-08-6	3 PPM		
Name	CAS-No.	OSHA PEL	OSHA STEL	
Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	25068-38-6			

glycidyl ether

phenol, polymer with formaldehyde,

Butyl glycidyl ether 2426-08-6 135 MGM3, 25 PPM

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

28064-14-4

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment, filter A.

EYE PROTECTION: Eye wash bottle with pure water. Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Protective gloves complying with EN 374: Nitrile rubber. Butyl rubber. PVA. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature). Long sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** Ensure adequate ventilation, especially in confined areas.

Not determined

9. Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Appearance: Clear Viscous Liquid

Physical State Liquid
Odor Mild

Odor threshold Not determined

pH Not determined

Melting point / freezing point (°C) Not determined

Boiling point/range (°C) 64 - N.D.

Flash Point, (°F / °C)

Evaporation rate

Not determined

Not determined

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive

limits - %(V)

Vapour Pressure Not determined

Vapour density Not determined

Relative density 1.15

Solubility in / Miscibility with water

Partition coefficient: n-octanol/water

Auto-ignition temperature (°C)

Not determined

Not determined

Not determined

Viscosity 1500 cps

Explosive properties Not determined

Oxidising properties Not determined

9.2 Other information

VOC Content g/l: Not determined

Specific Gravity (g/cm3) 1.146

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

No decomposition if stored and applied as directed.

10.3 Possibility of hazardous reactions

Amines cause exothermic reactions.

10.4 Conditions to avoid

Avoid temperatures above 40 °C, direct sunlight and contact with sources of heat. Do not freeze.

10.5 Incompatible materials

Oxidizing agents. Acids and bases.

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon monoxide, carbon dioxide and unburned hydrocarbons (smoke). No decomposition if stored and applied as directed.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat		0.000	0.000

phenol, polymer with 28064-14-4

5000 mg/kg. >2000 mg/kg, oral, rat

formaldehyde, glycidyl ether

rabbit

0.000

0.000

Additional Information:

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Ingestion may cause irritation to mucous membranes. Irritating to eyes and skin. May cause allergic skin reaction.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia): No information No information IC50 72hr (Algae): LC50 96hr (fish): No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	Chemical Name	EC50 48hr	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	Reaction product: bisphenol-A- (epichlorhydrin) epoxy resin (number average molecular weight <= 700)	1.8 mg/l	No information	1.5-7.7 mg/L
28064-14-4	phenol, polymer with formaldehyde, glycidyl ether	No information	No information	
2426-08-6	Butyl glycidyl ether	No information	No information	

13. Disposal Considerations

WASTE TREATMENT METHODS: Dispose of waste material at an approved hazardous waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Contaminated packaging to be disposed of as product. Fully drained containers which are drop- and scrape-free can be treated as industrial waste, and can possibly be recycled. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

14. Transport Information

14.1 UN number UN3082

14.2 UN proper shipping name Not regulated for transport according to U.S. DOT

Technical name Environmentally Hazardous Substances, Liquid, n.o.s. (Epoxy Resin)

14.3 Transport hazard class(es) 9

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Yes (Epoxy Resin)
14.6 Special precautions for user Not applicable
EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure), Germ cell mutagenicity

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

<u>Chemical Name</u> CAS-No. %

No SARA 313 substances exist in this product above de minimis concentrations.

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Not applicable

Not applicable

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

Chemical Name CAS-No. 4-(Hydroxymethyl)-1,3-dioxolan-2-one 931-40-8

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

Chemical Name CAS-No. 4-(Hydroxymethyl)-1,3-dioxolan-2-one 931-40-8

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 **Chemical Safety Assessment:**

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H226	Flammable liquid and vapour.
H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H335	May cause respiratory irritation.
H341	Suspected of causing genetic defects.
H351	Suspected of causing cancer.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Reasons for revision

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark; European Union Commission Regulation No. 1907/2006 on REACH as amended within Commission Regulation (EU) 2015/830;

European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation) and subsequent technical progress adaptations (ATP); EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes".

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

Safety Data Sheet Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

1.1 Product Identifier FPT-EM FS B Revision Date: 10/12/2022

Product Name: Epicon FS Mortar Component B Supersedes Date: 10/02/2018

1.2 Relevant identified uses of the substance or mixture and uses

advised against

Professional use only. For use by appropriately trained applicators. Advised against: Home DIY applications. Component of multi-component industrial grouts, mortars and

screeds.

1.3 Details of the supplier of the safety data sheet

Supplier: Prime Resins Inc.

2291 Plunkett Road Conyers, GA 30012

USA

Phone: 800-321-7212 Fax: 770-338-0936 www.primeresins.com

Datasheet Produced by: EHS@primeresins.com

1.4 Emergency telephone number: CHEMTREC +001 703 5273887 (Outside US)

CHEMTREC 1-800-424-9300 (Inside US)

Giftinformasjonen: +47 22 59 13 00

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4
Hazardous to the aquatic environment, Acute, category 1
Hazardous to the aquatic environment, Chronic, category 1
Carcinogenicity, category 1A
Reproductive_ToxicityF_category_1B
STOT, single exposure, category 1
Skin Corrosion, category 1
Skin Sensitizer, category 1

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

4,4'-isopropylidenediphenol, Diethylenetriamine, Tetraethylenepentamine, 2-piperazin-1-ylethylamine, quartz (silicon dioxide), Fatty acids, tall-oil, reaction products with tetraethylenepentamine, 4-nonylphenol, branched

HAZARD STATEMENTS

Skin Corrosion, category 1 Skin Sensitizer, category 1	H314-1 H317	Causes severe skin burns and eye damage. May cause an allergic skin reaction.
Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 1A	H332 H350-1A	Harmful if inhaled. May cause cancer.
Reproductive_ToxicityF_category_1B	H360F	May damage fertility.
STOT, single exposure, category 1	H370	Causes damage to organs.
Hazardous to the aquatic environment, Acute, category 1	H400	Very toxic to aquatic life.
Hazardous to the aquatic environment, Chronic, category 1	H410	Very toxic to aquatic life with long lasting effects.

PRECAUTION PHRASES

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash hands thoroughly after handling.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/ face protection.
P284	Wear respiratory protection.
P301+310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P301+330+331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P304+340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P307+311	IF exposed, call a POISON CENTER or doctor/physician.
P308+313	IF exposed or concerned: Get medical advice/attention.
P308+P313	IF exposed or concerned: Get medical advice/attention
P314	Get medical advice/attention if you feel unwell.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P363	Wash contaminated clothing before reuse.
P391	Collect spillage.
P403+233	Store in a well-ventilated place. Keep container tightly closed.

2.3 Other hazards

No Information

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

Hazardous ingredients					
Name According to EEC	EINEC No.	CAS-No.	<u>%</u>	<u>Classifications</u>	
quartz (silicon dioxide)	238-878-4	14808-60-7	50 - <75	H350-370	Carc. 1A, STOT SE 1
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	273-201-6	68953-36-6	10 - <25	H314-317-400-410	Aquatic Acute 1, Aquatic Chronic 1, Skin Corr. 1, Skin Sens. 1
2-piperazin-1- ylethylamine	205-411-0	140-31-8	2.5 - <10	H290-311-314-317-4 12	Acute Tox. 3 Dermal, Aquatic Chronic 3, Met. Corr 1, Skin Corr. 1, Skin Sens. 1
Diethylenetriamine	203-865-4	111-40-0	2.5 - <10	H302-312-314-317-3 30-335	Acute Tox. 1 Inhalation, Acute Tox. 4 Dermal, Acute Tox. 4 Oral, Skin Corr. 1, Skin Sens. 1A, STOT SE 3 RTI
4,4'- isopropylidenediphenol	201-245-8	80-05-7	2.5 - <10	H317-318-335-360F- 400-410	Aquatic Acute 1, Aquatic Chronic 1, Eye Dam. 1, Repr. 1B, Skin Sens. 1, STOT SE 3 RTI
4-nonylphenol, branched	284-325-5	84852-15-3	1.0 - <2.5	H302-314-361-400-4 10	Acute Tox. 4 Oral, Aquatic Acute 1, Aquatic Chronic 1, Repr. 2, Skin Corr. 1
glycerine	200-289-5	56-81-5	1.0 - <2.5	H372	STOT RE 1
Tetraethylenepentamine	203-986-2	112-57-2	1.0 - <2.5	H302-311-314-317-4 11	Acute Tox. 3 Dermal, Acute Tox. 4 Oral, Aquatic Chronic 2, Skin Corr. 1, Skin Sens. 1
titanium dioxide	236-675-5	13463-67-7	0.1 - <1.0	H351	Carc. 2

M-Factors
0
0
0
0
10
0
0
0
0

Additional Information:

The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice.

AFTER INHALATION: Move to fresh air. Give oxygen or artificial respiration if needed. Consult a physician after significant exposure. Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.

AFTER EYE CONTACT: Rinse thoroughly with plenty of water for at least 15 minutes and consult a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. If swallowed, call a poison control centre or doctor immediately.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

Irritating to eyes and skin. May be harmful if swallowed.

4.3 Indication of any immediate medical attention and special treatment needed

Immediate medical attention is required. No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam, Water Fog

FOR SAFETY REASONS NOT TO BE USED: Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

No Information

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Water sprayDry powderAlcohol-resistant foamCarbon dioxide (CO2). High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation. Use personal protective equipment.

6.2 Environmental precautions

Do not allow material to contaminate ground water system. Prevent product from entering drains.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Keep containers dry and tightly closed to avoid moisture absorption and contamination. Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment. Do not breathe vapours or spray mist. Wash thoroughly after handling. Do not get in eyes, on skin, or on clothing. Use only with adequate ventilation/personal protection.

PROTECTION AND HYGIENE MEASURES: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Direct sources of heat.

STORAGE CONDITIONS: Store in original container. Keep containers tightly closed in a cool, well-ventilated place. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight.

7.3 Specific end use(s)

No specific advice for end use available.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	CAS-No.	ACGIH TWA	ACGIH STEL	ACGIH Ceiling
quartz (silicon dioxide)	14808-60-7	0.025 MGM3		
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6			
2-piperazin-1-ylethylamine	140-31-8			
Diethylenetriamine	111-40-0	1 PPM		
4,4'-isopropylidenediphenol	80-05-7			
4-nonylphenol, branched	84852-15-3			
glycerine	56-81-5	10.0 MG/M3		
Tetraethylenepentamine	112-57-2			
titanium dioxide	13463-67-7	10 MGM3 10 MGM3		

<u>Name</u>	CAS-No.	OSHA PEL	OSHA STEL
quartz (silicon dioxide)	14808-60-7	0.05 MGM3	
Fatty acids, tall-oil, reaction products with tetraethylenepentamine	68953-36-6		
2-piperazin-1-ylethylamine	140-31-8		
Diethylenetriamine	111-40-0	4 MGM3, 1 PPM	
4,4'-isopropylidenediphenol	80-05-7		
4-nonylphenol, branched	84852-15-3		
glycerine	56-81-5	5 MGM3 15 MGM3	
Tetraethylenepentamine	112-57-2		

titanium dioxide 13463-67-7 15 MGM3

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. Use only with ventilation to keep levels below exposure guidelines reported in this document. User should test and monitor exposure levels to ensure all personnel are below guidelines. If not sure, or not able to monitor, use State or federally approved supplied air respirator. For silica containing coatings in a liquid state, and/or if no exposure limits are established above, air-supplied respirators are generally not required. Use NIOSH approved respiratory protection. If exposure exceeds occupational exposure limits, use an appropriate NIOSH approved full-face piece respirator, half-face piece respirator with splash goggles, or powered, filtered air-supplied hood. When the product is sprayed or heated without adequate ventilation, an approved MSHA/NIOSH positive-pressure, supplied-air respirator may be required.

EYE PROTECTION: Ensure that eyewash stations and safety showers are close to the workstation location. Tightly fitting safety goggles. Safety glasses with side-shields.

HAND PROTECTION: Solvent-resistant gloves (butyl-rubber)Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Impervious gloves. Nitrile rubber. NeopreneLong sleeved clothing. Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Wear suitable protective clothing. Protective shoes or boots.

ENGINEERING CONTROLS: Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas

9. Physical and Chemical Properties

9.1 Information or	basic physic	al and chemical	properties
--------------------	--------------	-----------------	------------

Appearance: Grey Viscous Liquid

Physical State Liquid
Odor Amine

Odor threshold Not determined

pH Alkaline

Melting point / freezing point (°C)

Not determined

Boiling point/range (°C) 220 - N.D.

Flash Point, (°F / °C)

Evaporation rate

Not determined

Not determined

Flammability (solid, gas)

Not determined

Upper/lower flammability or explosive Not determined

limits - %(V)

Vapour Pressure Not determined
Vapour density Not determined

Relative density 1.52

Solubility in / Miscibility with water Not determined

Partition coefficient: n-octanol/water

Not determined

Auto-ignition temperature (°C)

Not determined

Not determined

Viscosity 80,000 cps

Explosive properties

Not determined

Oxidising properties

Not determined

9.2 Other information

VOC Content g/l: Not determined

Specific Gravity (g/cm3) 0.000

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under normal storage and use conditions.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous polymerisation does not occur. Hazardous polymerisation may occur.

10.4 Conditions to avoid

Direct sources of heat.

10.5 Incompatible materials

Strong oxidizing agents.

10.6 Hazardous decomposition products

Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke.

11. Toxicological Information

11.1 Information on toxicological effects

Acute Toxicity:

Oral LD50: No information available.

Inhalation LC50: No information available.

Irritation: No information available.

Corrosivity: No information available.

Sensitization: No information available.

Repeated dose toxicity: No information available.

Carcinogenicity: No information available.

Mutagenicity: No information available.

Toxicity for reproduction: No information available.

STOT-single exposure: No information available.

STOT-repeated exposure: No information available.

Aspiration hazard: No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

CAS-No.	Chemical Name	Oral LD50	Dermal LD50	Vapor LC50	Gas LC50	Dust/Mist LC50
14808-60-7	quartz (silicon dioxide)	>2000 mg/kg			0.000	0.000
68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	4750 mg/kg oral, rat	8550		0.000	0.000
140-31-8	2-piperazin-1-ylethylamine	2108 mg/kg, oral, rat	866 mg/kg rabbit		0.000	0.000
111-40-0	Diethylenetriamine	1080 mg/kg, oral, rat	1090 mg/kg	10 mg/l		0.07
80-05-7	4,4'-isopropylidenediphenol	3250 mg/kg, oral, rat	3000 mg/kg, oral, rabbit		0.000	0.000
84852-15-3	4-nonylphenol, branched	580 mg/kg oral rat			0.000	0.000
13463-67-7	titanium dioxide	10000 mg/kg, oral (rat)			0.000	6,82 mg/l (rat) 4h

Additional Information:

Constituents of this product may include crystalline silica which, if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimis exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems. This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

12. Ecological Information

12.1 Toxicity:

EC50 48hr (Daphnia):

IC50 72hr (Algae):

No information
No information
No information

12.2 Persistence and degradability: No information

12.3 Bioaccumulative potential: No information

12.4 Mobility in soil: No information

12.5 Results of PBT and vPvB The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

assessment:

12.6 Other adverse effects: No information

CAS-No.	<u>Chemical Name</u>	EC50 48hr	IC50 72hr	LC50 96hr
14808-60-7	quartz (silicon dioxide)	No information	No information	
68953-36-6	Fatty acids, tall-oil, reaction products with tetraethylenepentamine	No information	No information	
140-31-8	2-piperazin-1-ylethylamine	58 mg/l	>1000 mg/L	2190 mg/l
111-40-0	Diethylenetriamine	780 mg/l	No information	430 mg/l
80-05-7	4,4'-isopropylidenediphenol	10.2 mg/l	No information	205 mg/l
84852-15-3	4-nonylphenol, branched	.035 mg/L	.0563 mg/L	.1383 mg/l
56-81-5	glycerine	No information	No information	
112-57-2	Tetraethylenepentamine	No information	No information	
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l

13. Disposal Considerations

13.1 WASTE TREATMENT METHODS: Do not burn, or use a cutting torch on, the empty drum. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of in accordance with local regulations. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport Information

14.1 UN number UN2735

14.2 UN proper shipping name Amines, liquid, corrosive, n.o.s. (polyamines, polyamidoamines)

Technical name Not applicable

14.3 Transport hazard class(es) 8

Subsidiary shipping hazard Not applicable

14.4 Packing group

14.5 Environmental hazards Not applicable
14.6 Special precautions for user Not applicable
EmS-No.: Not applicable

14.7 Transport in bulk according to Annex II of

MARPOL 73/78 and the IBC code

Not applicable

15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Reproductive toxicity, Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

Chemical Name CAS-No. %

4-nonylphenol, branched 84852-15-3 2.1

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

EPA Coating Category:

EPA VOC Content Limit (g/l):

Product VOC Content (g/l)

Thinning Recommendations:

Application Recommendations:

Not applicable

Not applicable

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u> <u>CAS-No.</u>

No NJ Right-To-Know components exist in this product.

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

No PA Right-To-Know components exist in this product.

California Proposition 65:

WARNING: Cancer - www.P65Warnings.ca.gov

WARNING: Reproductive Toxicant -- www.P65Warnings.ca.gov

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H290 May be corrosive to metals. H302 Harmful if swallowed. H311 Toxic in contact with skin. H312 Harmful in contact with skin.

^{*} As per the federal EPA definition for coating categories in 40 CFR 59.401.

^{**} Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

H314 Causes severe skin burns and eye damage.

H317 May cause an allergic skin reaction.

H318 Causes serious eye damage.

H330 Fatal if inhaled.

H335 May cause respiratory irritation.

H350 May cause cancer.

H351 Suspected of causing cancer.

H360F May damage fertility.

H361 Suspected of damaging fertility or the unborn child.

H370 Causes damage to organs.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.
 H411 Toxic to aquatic life with long lasting effects.
 H412 Harmful to aquatic life with long lasting effects.

Reasons for revision

Revision Description Changed

Substance Hazard Threshold % Changed

Substance and/or Product Properties Changed in Section(s):

01 - Identification

02 - Hazard Identification

08 - Exposure Controls/Personal Protection

09 - Physical and Chemical Properties

11 - Toxicological Information

14 - Transportation Information

15 - Regulatory Information

Composition Information Changed

Revision Statement(s) Changed

List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier

Acronym & Abbreviation Key:

CLP Classification, Labeling & Packaging Regulation

EC European Commission
EU European Union
US United States

CAS Chemical Abstract Service

EINECS European Inventory of Existing Chemical Substances

REACH Registration, Evaluation, Authorization of Chemicals Regulation

GHS Globally Harmonized System of Classification and Labeling of Chemicals

LTEL Long term exposure limit
STEL Short term exposure limit
OEL Occupational exposure limit

ppm Parts per million

mg/m3 Milligrams per cubic meter TLV Threshold Limit Value

ACGIH American Conference of Governmental Industrial Hygienists

OSHA Occupational Safety & Health Administration

PEL Permissible Exposure Limits
VOC Volatile organic compounds

g/l Grams per liter

mg/kg Milligrams per kilogram

N/A Not applicable LD50 Lethal dose at 50%

LC50 Lethal concentration at 50%

EC50 Half maximal effective concentration

IC50 Half maximal inhibitory concentration

PBT Persistent bioaccumulative toxic chemical

vPvB Very persistent and very bioaccumulative

EEC European Economic Community

ADR International Transport of Dangerous Goods by Road RID International Transport of Dangerous Goods by Rail

UN United Nations

IMDG International Maritime Dangerous Goods Code
IATA International Air Transport Association

MARPOL International Convention for the Prevention of Pollution From Ships, 1973 as

modified by the Protocol of 1978

IBC International Bulk Container
RTI Respiratory Tract Irritation

NE Narcotic Effects

IMO International Maritime Organization

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.