Safety Data Sheet

Prepared in Accordance with HCS 29 C.F.R. 1910.1200



1. Identification of the Substance/Mixture and the Company/Undertaking

| 1.1 | Product Identifier | RM-PF940 | Revision Date: | 10/31/2024 | | |
|-----|---|--|--|---------------|--|--|
| | Product Name: | Prime Flex 940 | Supersedes Date: | 09/13/2023 | | |
| 1.2 | Relevant identified uses of the substance or mixture and uses advised against | See Technical Datasheet. For use by a others than recommended | appropriately trained applicators. Adv | ised against: | | |
| 1.3 | Details of the supplier of the safety | Details of the supplier of the safety data sheet | | | | |
| | Supplier: | Prime Resins Inc. 2291 Plunkett Road Conyers, GA 30012 USA Phone: 800-321-7212 Fax: 770-338-0936 www.primeresins.com | | | | |
| | Datasheet Produced by: | EHS@primeresins.com | | | | |
| 1.4 | Emergency telephone number: | CHEMTREC +001 703 5273887 (Outs CHEMTREC 1-800-424-9300 (Inside L | | | | |

2. Hazard Identification

2.1 Classification of the substance or mixture

Acute Toxicity, Inhalation, category 4 Carcinogenicity, category 2 Serious Eye Damage, category 1 Respiratory Sensitizer, category 1 Skin Irritation, category 2 Skin Sensitizer, category 2 STOT, repeated exposure, category 2 STOT, single exposure, category 3, RTI

2.2 Label elements

Symbol(s) of Product



Signal Word

Danger

Named Chemicals on Label

γ-Butyrolactone, 4,4'-methylenediphenyl diisocyanate, Diphenylmethane-2,4'-diisocyanate, Methylenediphenyl diisocyanate, oxirane, methyl-, polymer with 1,1'-methylenebis[isocyanatobenzene], methyloxirane polymer with oxirane ether with oxybis [propanol] (2:1), and oxirane

HAZARD STATEMENTS

| Skin Irritation, category 2 | H315 | Causes skin irritation. |
|--|--------------|---|
| Skin Sensitizer, category 1 | H317 | May cause an allergic skin reaction. |
| Serious Eye Damage, category 1 | H318 | Causes serious eye damage. |
| Acute Toxicity, Inhalation, category 4 | H332 | Harmful if inhaled. |
| Respiratory Sensitizer, category 1 | H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| STOT, single exposure, category 3, RTI | H335 | May cause respiratory irritation. |
| Carcinogenicity, category 2 | H351 | Suspected of causing cancer. |
| STOT, repeated exposure, category 2 | H373 | May cause damage to organs through prolonged or repeated exposure. |
| PRECAUTION PHRASES | | |
| | P260 | Do not breathe dust/fume/gas/mist/vapours/spray. |
| | P280 | Wear protective gloves/protective clothing/eye protection/ face protection. |
| | P284 | Wear respiratory protection. |
| | P285 | In case of inadequate ventilation wear respiratory protection. |
| | P301+310 | IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. |
| | P302+352 | IF ON SKIN: Wash with plenty of soap and water. |
| | P304+340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| | P305+351+338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing. |
| | P308+313 | IF exposed or concerned: Get medical advice/attention. |
| | P314 | Get medical advice/attention if you feel unwell. |
| | P333+313 | If skin irritation or rash occurs: Get medical advice/attention. |
| | P341 | If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. |
| | P342+311 | If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician. |

2.3 Other hazards

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

Results of PBT and vPvB assessment:

The product does not meet the criteria for PBT/VPvB in accordance with Annex XIII.

3. Composition/Information On Ingredients

3.2 Mixtures

| Hazardous ingredients | | | | | |
|---|-------------------------------|----------------------------|----------------------|---|---|
| Name According to EEC 4,4'-methylenediphenyl diisocyanate | <u>EINEC No.</u> 202-966-0 | <u>CAS-No.</u> 101-68-8 | <u>%</u> 10 - <25 | Classifications H315-317-319-332-3 34-335-351-373 | Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1A, STOT RE 2, STOT SE 3 RTI |
| oxirane, methyl-, polymer with 1,1'- methylenebis [isocyanatobenzene], methyloxirane polymer with oxirane ether with oxybis[propanol] (2:1), and oxirane | | 157937-75-2 | 10 - <25 | H315-317-319-332-3 34-335-351-373 | Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 RTI |
| Methylenediphenyl diisocyanate | 247-714-0 | 26447-40-5 | 10 - <25 | H315-317-319-332-3 34-335-351-373 | Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 RTI |
| γ-Butyrolactone | 202-509-5 | 96-48-0 | 2.5 - <10 | H302-318-336 | Acute Tox. 4 Oral, Eye Dam. 1, STOT SE 3 NE |
| Diphenylmethane-2,4'- diisocyanate | 227-534-9 | 5873-54-1 | 1.0 - <2.5 | H315-317-319-332-3 34-335-351-373 | Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 RTI |
| CAS-No. 101-68-8 157037 75 2 | <u>M-Factors</u> | | | | |

157937-75-2 26447-40-5 96-48-0 5873-54-1

Additional Information: The text for GHS Hazard Statements shown above (if any) is given in Section 16.

4. First-aid Measures

4.1 Description of First Aid Measures

GENERAL NOTES: When symptoms persist or in all cases of doubt seek medical advice. Show this safety data sheet to the doctor in attendance.

AFTER INHALATION: Remove person to fresh air. If signs/symptoms continue, get medical attention.

AFTER SKIN CONTACT: Use a mild soap if available. Do not use solvent or thinners to clean skin. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician. AFTER EYE CONTACT: Consult a physician. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses.

AFTER INGESTION: Gently wipe or rinse the inside of the mouth with water. Never give anything by mouth to an unconscious person. Obtain medical attention. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel.

Self protection of the first aider:

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

4.2 Most important symptoms and effects, both acute and delayed

May cause damage to organs through prolonged or repeated exposure. Harmful by inhalation. Irritating to respiratory system. Limited evidence of a carcinogenic effect. Irritating to eyes and skin. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact.

4.3 Indication of any immediate medical attention and special treatment needed

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

5. Fire-fighting Measures

5.1 Extinguishing Media:

Carbon Dioxide, Dry Chemical, Foam

FOR SAFETY REASONS NOT TO BE USED: Do not use a solid water stream as it may scatter and spread fire. Alcohol, Alcohol based solutions, any other media not listed above.

5.2 Special hazards arising from the substance or mixture

Carbon monoxide, carbon dioxide, nitrogen oxide, cyanides, isocyanate vapours.

5.3 Advice for firefighters

Use water spray to cool unopened containers. Fire will produce dense black smoke containing hazardous combustion products (see section 10). In the event of fire, wear self-contained breathing apparatus. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

6. Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. For personal protection see section 8.2. Ensure adequate ventilation. Use personal protective equipment. Keep people away from and upwind of spill/leak.

6.2 Environmental precautions

Discharge into the environment must be avoided. Prevent product from entering drains. Local authorities should be advised if significant spillages cannot be contained.

6.3 Methods and material for containment and cleaning up

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13). Refer to protective measures listed in sections 7 and 8. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas.

6.4 Reference to other sections

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 8 and 13 for further information.

7. Handling and Storage

7.1 Precautions for safe handling

INSTRUCTIONS FOR SAFE HANDLING: Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this preparation is being used. Provide sufficient air exchange and/or exhaust in work rooms. Wear personal protective equipment. Do not breathe vapours or spray mist. Avoid contact with skin and eyes. Apply technical measures to comply with the occupational exposure limits (see section 8). **PROTECTION AND HYGIENE MEASURES:** Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Handle in accordance with good industrial hygiene and safety practice. Keep working clothes separately. Keep away from food, drink and animal feedingstuffs. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

CONDITIONS TO AVOID: Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze. **STORAGE CONDITIONS:** Keep out of the reach of children. Keep at temperatures between 10 and 30 °C. Store in original container. Keep container closed when not in use. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. Keep away from food, drink and animal feeding stuffs.

7.3 Specific end use(s)

Component of multicomponent coatings. The mixing and application to be in accordance with the technical data sheets.

8. Exposure Controls/Personal Protection

8.1 Control parameters

Ingredients with Occupational Exposure Limits

(US)

| Name | CAS-No. | ACGIH TWA | ACGIH STEL | ACGIH Ceiling |
|--|---------------------------------------|-----------------------------|------------------|---------------|
| 4,4'-methylenediphenyl diisocyanate | 101-68-8 | 0.005 PPM | | |
| oxirane, methyl-, polymer with 1,1'- methylenebis[isocyanatobenzene], methyloxirane polymer with oxirane e with oxybis[propanol] (2:1), and oxiran | | | | |
| Methylenediphenyl diisocyanate | 26447-40-5 | | | |
| γ-Butyrolactone | 96-48-0 | | | |
| Diphenylmethane-2,4'-diisocyanate | 5873-54-1 | | | |
| Name | | | | |
| | | | | |
| Name | <u>CAS-No.</u> | <u>OSHA PEL</u> | <u>OSHA STEL</u> | |
| 4,4'-methylenediphenyl diisocyanate | <u>CAS-No.</u> 101-68-8 | OSHA PEL 0.02 PPM-CEILIN | <u>OSHA STEL</u> | |
| | 101-68-8 157937-75-2 ther | | <u>OSHA STEL</u> | |
| 4,4'-methylenediphenyl diisocyanate oxirane, methyl-, polymer with 1,1'- methylenebis[isocyanatobenzene], methyloxirane polymer with oxirane e | 101-68-8 157937-75-2 ther | | <u>OSHA STEL</u> | |
| 4,4'-methylenediphenyl diisocyanate oxirane, methyl-, polymer with 1,1'- methylenebis[isocyanatobenzene], methyloxirane polymer with oxirane e with oxybis[propanol] (2:1), and oxiran | 101-68-8 157937-75-2 ther ne | | <u>OSHA STEL</u> | |

FURTHER INFORMATION: Refer to the regulatory exposure limits for the workforce enforced in each country.

8.2 Exposure controls

Personal Protection

RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required. In case of insufficient ventilation wear suitable respiratory equipment. Combination filter: A2-P2.

EYE PROTECTION: Safety glasses with side-shields conforming to EN 166.

HAND PROTECTION: Use chemical resistant gloves (EN 374): Butyl rubber; thickness >= 0,5 mm; breakthrough time >=60 min. Use chemical resistant gloves (EN 374): Nitrile rubber; thickness >=0,5 mm; breakthrough time >= 480 min. Isocyanates can harden gloves and increase the risk of their splitting. Gloves should be discarded and replaced if there is any indication of degradation or chemical breakthrough. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Be aware that in daily use the durability of a chemical resistant protective glove can be notably shorter than the break through time measured according to EN 374, due to the numerous outside influences (e.g. temperature).

Body Protection: Long sleeved clothing.

Remove and wash contaminated clothing before re-use.

OTHER PROTECTIVE EQUIPMENT: Ensure that eyewash stations and safety showers are close to the workstation location. **ENGINEERING CONTROLS:** At temperatures below 30°C, provide a good standard of general ventilation. At temperatures over 30°C - and always if sprayed - exhaust ventilation is required. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

9. Physical and Chemical Properties

| 9.1 | Information on basic physical and chemical properties Appearance: | S Not determined |
|-----|--|--------------------|
| | Physical State | Liquid |
| | Odor | Pungent |
| | Odor threshold | Not determined |
| | рН | Not determined |
| | Melting point / freezing point (°C) | Not determined |
| | Boiling point/range (°C) | 64 - N.D. |
| | Flash Point, (°F / °C) | Not determined |
| | Evaporation rate | Pale yellow liquid |
| | Flammability (solid, gas) | Not determined |
| | Upper/lower flammability or explosive limits - %(V) | Not determined |
| | Vapour Pressure | Not determined |
| | Vapour density | Not determined |
| | Relative density | 1.116 |
| | Solubility in / Miscibility with water | Not determined |
| | Partition coefficient: n-octanol/water | Not determined |
| | Auto-ignition temperature (°C) | Not determined |
| | Decomposition temperature (°C) | Not determined |
| | Viscosity | 500 cps |
| | Explosive properties | Not determined |
| | Oxidising properties | Not determined |
| 9.2 | Other information | |
| | VOC Content g/l: | Not determined |
| | Specific Gravity (g/cm3) | 1.116 |
| | | |

10. Stability and Reactivity

10.1 Reactivity

No reactivity hazards known under recommended storage and use conditions.

10.2 Chemical stability

Stable under recommended storage conditions. Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

10.3 Possibility of hazardous reactions

Polymerises at about 200°C with evolution of CO2. Amines and alcohols cause exothermic reactions. Preparation reacts slowly with water resulting in evolution of CO2.

10.4 Conditions to avoid

Avoid temperatures above 30 °C, direct sunlight and contact with sources of heat. Do not freeze.

10.5 Incompatible materials

Keep away from oxidising agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

10.6 Hazardous decomposition products

In case of fire hazardous decomposition products may be produced such as: Carbon dioxide (CO2), carbon monoxide (CO), oxides of nitrogen (NOx), dense black smoke. Preparation reacts slowly with water resulting in evolution of CO2. Evolution of CO2 in closed containers causes overpressure and produces a risk of bursting.

11. Toxicological Information

11.1 Information on toxicological effects

| Acute Toxicity: | |
|----------------------------|---------------------------|
| Oral LD50: | No information available. |
| Inhalation LC50: | No information available. |
| 1. 1. 1. | No information available. |
| Irritation: | |
| Corrosivity: | No information available. |
| • | |
| Sensitization: | No information available. |
| Repeated dose toxicity: | No information available. |
| Carcinogenicity: | No information available. |
| | |
| Mutagenicity: | No information available. |
| Toxicity for reproduction: | No information available. |
| STOT-single exposure: | No information available. |
| STOT-repeated exposure: | No information available. |
| Aspiration hazard: | No information available. |

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below:

| CAS-No. | Chemical Name | Oral LD50 | Dermal LD50 | Vapor LC50 | Gas LC50 | Dust/Mist LC50 |
|-------------|---|---------------------|---------------|-----------------------|----------|----------------|
| 101-68-8 | 4,4'-methylenediphenyl diisocyanate | 15000 mg/kg oral | >9400 mg/kg | 43 ppm vapor 4 hrs | 0.000 | 0.000 |
| 157937-75-2 | oxirane, methyl-, polymer with 1,1'-methylenebis [isocyanatobenzene], methyloxirane polymer with oxirane ether with oxybis [propanol] (2:1), and oxirane | >10000 mg/kg | | 0 | 0.000 | 0.000 |
| 26447-40-5 | Methylenediphenyl diisocyanate | 15000 mg/kg oral | | 43 ppm vapor 4hrs | 0.000 | 0.000 |
| 96-48-0 | γ-Butyrolactone | 1,540 mg/kg | > 5,000 mg/kg | | 0.000 | 0.000 |

| 5873-54-1 | Diphenylmethane-2,4'- |
|-----------|-----------------------|
| 3073-34-1 | diisocvanate |

1.5 mg/l (4 h, Aerosol. rat)

Additional Information:

Toyloltu

10 1

In the case of sensitisation to any of the ingredients, it is inadvisable to work with the product. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitization of susceptible persons. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates. Isocyanates may cause acute irritation and/or sensitisation of the respiratory system leading to tightness of the chest, wheeziness and an asthmatic condition.

12. Ecological Information

| 12.1 | Toxici | ty: | | | | |
|-------|-----------------|---|---------|-------------------------|----------------------|----------------------------------|
| | EC | 50 48hr (Daphnia): | No info | ormation | | |
| | IC5 | 0 72hr (Algae): | No inf | ormation | | |
| | LC5 | 50 96hr (fish): | No inf | ormation | | |
| 12.2 | Persis | tence and degradability: | No inf | ormation | | |
| 12.3 | Bioaco | cumulative potential: | No inf | ormation | | |
| 12.4 | Mobili | ty in soil: | No inf | ormation | | |
| 12.5 | Result asses | ts of PBT and vPvB sment: | The pr | oduct does not meet the | e criteria for PBT/V | PvB in accordance with Annex XII |
| 12.6 | Other | adverse effects: | No inf | ormation | | |
| CAS- | <u>No.</u> | Chemical Name | | <u>EC50 48hr</u> | <u>IC50 72hr</u> | <u>LC50 96hr</u> |
| 101-6 | 8-8 | 4,4'-methylenediphenyl diisocyanate | | >1000 mg/l | No information | >1000 mg/l |
| 15793 | 37-75-2 | oxirane, methyl-, polymer with 1,1'- methylenebis[isocyanatobenzene], methyloxirane polymer with oxirane eth oxybis[propanol] (2:1), and oxirane | er with | No information | No information | >1000 mg/l |
| 26447 | 7-40-5 | Methylenediphenyl diisocyanate | | No information | No information | |
| 96-48 | -0 | γ-Butyrolactone | | > 500 mg/l (Water flea) | No information | > 220 mg/l (Golden orfe) |
| 5873 | -54-1 | Diphenylmethane-2,4'-diisocyanate | | No information | No information | >1000 mg/l |

13.1 WASTE TREATMENT METHODS: Dispose of waste material at an approved hazardous waste treatment/disposal facility in accordance with applicable local state, and federal regulations. Do not dispose of waste with normal garbage, or to sewer systems. Contaminated packaging to be disposed of as product. Empty containers should be taken to an approved waste handling site for recycling or disposal. The product should not be allowed to enter drains, water courses or the soil.

14. Transport Information

| 17. | | |
|------|---|---|
| 14.1 | UN number | Not applicable |
| 14.2 | UN proper shipping name | Not regulated for transport according to U.S. DOT, ADR/RID, IMDG, and IATA regulations. |
| | Technical name | Not applicable |
| 14.3 | Transport hazard class(es) | Not applicable |
| | Subsidiary shipping hazard | Not applicable |
| 14.4 | Packing group | Not applicable |
| 14.5 | Environmental hazards | Not applicable |
| 14.6 | Special precautions for user | Not applicable |
| | EmS-No.: | Not applicable |
| 14.7 | Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code | Not applicable |

15. Regulatory Information

^{15.1} Safety, health and environmental regulations/legislation for the substance or mixture:

U.S. Federal Regulations: As follows -

CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

Sara Section 313:

 This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S.

 Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

 Chemical Name
 <u>%</u>

4,4'-methylenediphenyl diisocyanate

Toxic Substances Control Act:

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

101-68-8

19.95

No TSCA 12(b) components exist in this product.

U.S. Clean Air Act:

| EPA Coating Category: | Not applicable |
|------------------------------|----------------|
| EPA VOC Content Limit (g/l): | Not determined |
| Product VOC Content (g/l) | Not applicable |
| Thinning Recommendations: | Not applicable |
| Application Recommendations: | Not applicable |

* As per the federal EPA definition for coating categories in 40 CFR 59.401.

** Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

U.S. State Regulations: As follows -

New Jersey Right-to-Know:

The following materials are non-hazardous, but are among the top five components in this product.

| Chemical Name | CAS-No. |
|--------------------------------------|---------|
| Non-hazardous, supplier trade secret | unknown |
| No Chemical Name Found | |

Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

| Chemical Name | CAS-No. |
|---|-----------|
| Non-hazardous, supplier trade secret | unknown |
| No Chemical Name Found dimethyl glutarate | 1119-40-0 |
| No Chemical Name Found dimethyl glutarate | 1119-40-(|

California Proposition 65:

No Proposition 65 Chemicals exist in this product.

International Regulations: As follows -

* Canadian DSL:

All chemical ingredients included on inventory or exempt.

15.2 Chemical Safety Assessment:

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

16. Other Information

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

- H302 Harmful if swallowed.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.

| H319 | Causes serious eye irritation. |
|------|--|
| H332 | Harmful if inhaled. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H335 | May cause respiratory irritation. |
| H336 | May cause drowsiness or dizziness. |
| H351 | Suspected of causing cancer. |
| H373 | May cause damage to organs through prolonged or repeated exposure. |

Reasons for revision

Substance and/or Product Properties Changed in Section(s): 02 - Hazard Identification 03 - Composition/Information On Ingredients 08 - Exposure Controls/Personal Protection 09 - Physical and Chemical Properties 11 - Toxicological Information 15 - Regulatory Information Revision Statement(s) Changed

List of References:

.

This Safety Data Sheet was compiled with data and information from the following sources:

- The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark.
- Joint Research Centre in Ispra, Italy.
- Regulation (EC) 1272/2008 with subsequent amendments.
- Regulation (EC) 1272/2006 with subsequent amendments.
- Commission Regulation (EU) 2020/878
- EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"
- Safety Data Sheet from raw material supplier
- The classification declared in sec. 2.2 is based on the calculation methods set out in Annex I and Annex II of the CLP Reg. 1272/2008 on the composition of the formula.

Acronym & Abbreviation Key:

| CLP | Classification, Labeling & Packaging Regulation |
|--------|--|
| EC | European Commission |
| EU | European Union |
| US | United States |
| CAS | Chemical Abstract Service |
| EINECS | European Inventory of Existing Chemical Substances |
| REACH | Registration, Evaluation, Authorization of Chemicals Regulation |
| GHS | Globally Harmonized System of Classification and Labeling of Chemicals |
| LTEL | Long term exposure limit |
| STEL | Short term exposure limit |
| OEL | Occupational exposure limit |
| ppm | Parts per million |
| mg/m3 | Milligrams per cubic meter |
| TLV | Threshold Limit Value |
| ACGIH | American Conference of Governmental Industrial Hygienists |
| OSHA | Occupational Safety & Health Administration |
| PEL | Permissible Exposure Limits |
| VOC | Volatile organic compounds |
| g/l | Grams per liter |
| mg/kg | Milligrams per kilogram |
| N/A | Not applicable |
| LD50 | Lethal dose at 50% |
| LC50 | Lethal concentration at 50% |
| EC50 | Half maximal effective concentration |

Date Printed: 10/31/2024

| IC50 | Half maximal inhibitory concentration |
|----------|---|
| PBT | Persistent bioaccumulative toxic chemical |
| vPvB | Very persistent and very bioaccumulative |
| EEC | European Economic Community |
| ADR | International Transport of Dangerous Goods by Road |
| RID | International Transport of Dangerous Goods by Rail |
| UN | United Nations |
| IMDG | International Maritime Dangerous Goods Code |
| IATA | International Air Transport Association |
| MARPOL | International Convention for the Prevention of Pollution From Ships, 1973 as |
| | modified by the Protocol of 1978 |
| IBC | International Bulk Container |
| RTI | Respiratory Tract Irritation |
| NE | Narcotic Effects |
| IMO | International Maritime Organization |
| Note P: | The classification as a carcinogen or mutagen need not apply; the substance |
| | contains less than 0,1 % w/w benzene |
| Note 10: | The classification as a carcinogen by inhalation applies only to mixtures in |
| | powder form containing 1 $\%$ or more of titanium dioxide which is in the form of |
| | or incorporated in particles with aerodynamic diameter \leq 10 µm. |
| | |

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.

Date Printed: 10/31/2024